

T 2 Serie • Series

Polytetrafluorethylen (PTFE)
Verstärkte Innenseele • heavy wall

Edelstahldraht • Stainless Steel wire

Edelstahldraht • Stainless Steel wire



Artikel Nr. Article ref.	Größe Size	Innen-Ø Inner-Ø		Außen-Ø Outer-Ø		Biegeradius ³⁾ Bend Radius ³⁾		Arbeitsdruck ²⁾ Working Pressure ²⁾		Platzdruck Burst Pressure		Gewicht Weight kg/100m	Produktionslänge ⁴⁾ Product Length ⁴⁾ m
		mm	inch	mm	inch	mm	inch	bar	psi	bar	psi		
▶ T2-06	4	6,3	1/4	11,5	0,45	75	2,95	275	4000	1100	16000	23,0	40 - 100
▶ T2-08	5	8,0	5/16	13,0	0,51	100	3,94	250	3600	1000	14500	30,0	40 - 100
▶ T2-10	6	10,3	3/8	16,0	0,63	120	4,72	225	3300	900	13000	38,0	40 - 100
▶ T2-13	8	12,7	1/2	18,8	0,74	135	5,31	190	2750	760	11000	46,0	40 - 100
▶ T2-16	10	15,6	5/8	21,8	0,86	160	6,30	175	2500	700	10200	58,0	40 - 70
▶ T2-20	12	20,5	3/4	27,6	1,09	200	7,87	150	2200	600	8700	84,0	40 - 60
▶ T2-25	16	25,0	1	31,5	1,24	250	9,84	130	1900	520	7500	92,0	40 - 60
▶ T2-32	20	32,0	1 1/4	39,5	1,56	500	19,70	70	1000	280	4100	130,0	10 - 20
▶ T2-40	24	38,0	1 1/2	48,0	1,89	850	33,46	50	725	200	2900	190,0	4 - 9

1), 2), 3), 4) Siehe Seite 36 / See page 36.

Temperaturbeständigkeit : • **temperature resistant** : -70°C bis • to 200°C.



Konstruktionsänderungen vorbehalten.
Stand 09/2015.
Subject to change.
Printed 09/2015.